



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
28.11.2001 Bulletin 2001/48

(51) Int Cl.7: **F25B 9/14**

(21) Application number: 01304519.0

(22) Date of filing: 23.05.2001

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Wang, Chao**
Manlius, New York 13104 (US)

(74) Representative: **Jones, Graham Henry**
Graham Jones & Company
77 Beaconsfield Road
Blackheath, London SE3 7LG (GB)

(30) Priority: 25.05.2000 US 579148


(71) Applicant: **Cryomech, Inc.**
Syracuse, New York 13211 (US)

(54) **Pulse-tube cryorefrigeration apparatus using an integrated buffer volume**

(57) A component for use in pulse tube cryorefrigerators which integrates the reservoirs (buffer volumes) (50,51,52,53) as well as the housing for the rotary valve (20) and valve plate (21) and drive motor (30) into a convenient, unified assembly. Other components required

by the pulse-tube refrigerators, such as the heat sink (110), orifices (40), phase shifting valves, connecting tubing (105), etc., may also be integrated into the buffer volume/valve/motor housing (80) within the teachings of the invention.

FIG. 1



Description

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

[0001] The invention pertains to the field of cryorefrigeration. More particularly, the invention pertains to an integrated component for a pulse tube cryorefrigerator.

DESCRIPTION OF RELATED ART

[0002] Typical closed-cycle expansion cryogenic refrigerators include the Stirling, Gifford-McMahon and pulse tube types, all of which provide cooling through the alternating compression and expansion of a cryogen, with a consequent reduction of its temperature. Stirling and Gifford-McMahon regenerative refrigerators use displacers to move a cryogen (usually helium) through their regenerators, exhaust the heat in the return gas to the compressor package. The noise and vibration induced by the displacer creates problems, and the wear of the seals on the displacer require periodic maintenance and replacement.

[0003] Therefore, it is highly desirable to invent cryorefrigeration devices that generate less vibration and less acoustic noise than prior art cryorefrigerators. It is also desirable to decrease the number of moving parts used in cryorefrigeration devices and to significantly increase the required maintenance intervals.

[0004] Pulse tube refrigerators are a known alternative to the Stirling and Gifford-McMahon types, which do not use a mechanical displacer.

[0005] A pulse tube is essentially an adiabatic space wherein the temperature of the working fluid is stratified, such that one end of the tube is warmer than the other. A pulse tube refrigerator operates by cyclically compressing and expanding a cryogen in conjunction with its movement through heat exchangers. Heat is removed from the system upon the expansion of the cryogen in the gas phase.

[0006] Prior art single-stage valved pulse tube cryorefrigerators generally include a pulse tube, a rotary valve to generate the oscillating compression-expansion cycle, a reservoir to contain the expanding cryogen gas, orifices for the movement and phasing of the gas between the reservoir or buffer volume and the rest of the system, and a regenerator for absorbing heat temporarily and reversibly. Single stage pulse tube cryorefrigerators are generally capable of reaching temperatures above 20° K, and achieving lower temperatures has in the past required staging of the pulse tubes. U.S. Patent No. 3,237,421 to Gifford and other prior art publications disclose multistage pulse tube cryorefrigerators.

[0007] Prior art two-stage pulse tube cryorefrigerators generally include, in addition to the foregoing components, a first-stage pulse tube, a first-stage regenerator, a second-stage pulse tube, a second-stage regenerator

and first and second cooling stages.

[0008] Although an improvement over mechanical displacement devices, prior art pulse tube cryorefrigerators were ungainly arrangements of separate components, which leads to inefficiency and difficulty in manufacture and maintenance.

[0009] Pulse tube coolers can be employed in a wide variety of applications from civilian to government to military. Most of the applications below are dependent on the availability of a cheap cryocooler with a long life - long life is a unique advantage of the pulse tube cooler.

- Sensors: Infrared; atmospheric studies, thermal losses, pollution monitoring, process monitoring, night vision, missile guidance, missile surveillance, Gamma-ray, monitor nuclear activity
- Semiconductors in computers: (large speed gain at small cost penalty, temperatures around 100 - 200 K)
- Hi-Tc superconductors: Cellular phone base stations (more channels, temperatures under 80 K), High speed computers, SQUID magnetometers, heart and brain studies
- Magnets: maglev trains, mine sweeping
- Cryopumps for the semiconductor industry
- Cryogenic catheters, Cryosurgery
- Liquefaction of gases: Helium, Hydrogen, Neon, Nitrogen, Argon Oxygen, Natural Gas, etc. - remote wells or peak shaving (providing extra gas at peak loads to minimize steady pipeline capacity) or for fleet vehicles

[0010] Perhaps the application of cryorefrigeration which is most familiar to the public is its use in Magnetic Resonance Imaging (hereinafter "MRI"). MRI is an imaging technique used widely within the medical field to produce high quality images of the inside of a human body.

[0011] Generally, the most expensive component of a MRI system is the imaging magnet, which is typically an electromagnet made from a superconducting material. When cooled to a temperature near absolute zero (*i.e.*, -273.15° C or 0° K), the superconducting wire in the magnet's coil has an electrical resistance approaching zero. Therefore, MRI imaging magnets are usually maintained at a temperature of 4.2° K using liquid helium.

[0012] Typically, the main superconducting coils of a MRI imaging magnet are enclosed in a pressure vessel contained within an evacuated vessel (*i.e.*, Dewar vessel), and superconducting temperatures are obtained by boiling a liquid cryogen, such as liquid helium, within the

pressure vessel. Because distribution, storage and handling of liquid helium is difficult and costly, mechanical displacement cryorefrigerators, such as the Gifford-McMahon type, typically are used to condense and recycle the helium gas generated by boiling the liquid cryogen.

[0013] One problem associated with cryorefrigerators using displacers is that the motion of the displacer creates a series of repetitive knocking sounds and mechanical vibrations, which become especially rapid as the magnet in the MRI is cycled on and off to generate the magnetic field gradients that are used to collect information regarding the molecular structure of a patient's body. The MRI equipment thus generates high acoustic noise levels, and also vibrates. Because of the volume of this noise, it is recommended that patients undergoing MRI use hearing protection devices. In fact, some MRI imaging sites even go to such lengths as to provide an airplane-like audio headphone system for their patients, in order to protect their hearing and mask the acoustic noise, which may agitate or frighten the patient.

SUMMARY OF THE INVENTION

[0014] The present invention is a component for use in pulse tube cryorefrigerators which integrates one or more of the reservoirs (buffer volumes) as well as the housing for the rotary valve and valve plate and drive motor into a convenient, unified assembly. Other components required by the pulse-tube refrigerators, such as the heat sink, orifices, phase shifting valves, connecting tubing, etc., may also be integrated into the buffer volume/valve/motor housing within the teachings of the invention.

[0015] Cryorefrigerators using the novel component have increased efficiency, reduced manufacturing cost, and increased compatibility with varied cryostats due to the compactness of the component.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016]

Fig. 1 shows a block diagram of a single-stage cryorefrigeration apparatus of the present invention.

Fig. 2 shows a block diagram of a two-stage cryorefrigeration apparatus of the present invention.

Fig. 3 shows a perspective view of a cryorefrigerator of the invention.

Figs. 4a and 4b show side cut-away and top drawings, respectively, of an integrated pressure control housing and buffer volume, for use in a single-stage cryorefrigerator.

Figs. 5a and 5b show side cut-away and top drawings, respectively, of an integrated pressure control

housing and buffer volume with an integrated secondary buffer volume, for a two-stage cryorefrigerator.

Figs. 6a and 6b show side cut-away and top drawings, respectively, of an integrated pressure control housing and buffer volume, with an external secondary buffer volume, for use in a two-stage cryorefrigerator.

DETAILED DESCRIPTION OF THE INVENTION

[0017] The invention is component for a single, double or multiple-stage pulse tube cryorefrigeration apparatus which integrates a number of the parts into a single housing, and cryorefrigerators using the component. The overall system using the component may be used as a stand alone cryorefrigerator or in a cryostat in conjunction with a larger cryorefrigeration system.

[0018] Referring to Fig. 1, a single-stage cryorefrigeration apparatus of the invention includes a rotary valve 20 or other devices for controlling pressure oscillation, the actuator for the valve 20, shown here as motor 30, and a reservoir or buffer volume 50, all integrated within housing 80, thereby forming a single integrated unit. Flow channels 105 connect the orifices 40, valve 14, reservoir 50 and external components 60 and 70.

[0019] The integrated motor housing and reservoir is made from any suitable material capable of withstanding high pressure (*i.e.*, greater than 300 psig), such as machined aluminum, copper, bronze, brass or stainless steel. In a preferred embodiment, the housing is machined from a single block of 6061-T6 aluminum.

[0020] The single stage pulse tube cryorefrigerator is a simple heat pump that pumps heat from a cooling load (not shown) to a heat sink 110, and thus to the ambient environment. Compressor 10, typically a piston type compressor, delivers cryogen under pressure to the pressure oscillation controller, such as, for example, a rotary valve 20 rotated by motor 30. Housing 80, which optionally serves as a heat sink 110, integrates pressure oscillation controlling means 20, its power source 30, and reservoir 50 into a single unit, with the parts connected by flow channels 105. Preferably, the orifices 40 are also integrated into the housing 80.

[0021] In operation, compressor 10 delivers cryogen (usually helium) under pressure to pressure oscillation controlling means 20, thereby causing an alternating mass flow throughout the pulse tube refrigerator. As shown in figure 1, as the rotary valve 20 rotates, the bores 14 through the body 15 of the rotary valve 20 alternately connect the regenerator inlet connection 12 to the pressurized cryogen inlet 11 connected to the compressor 10 output line 17 (the valve is shown in this position), and to the lower pressure cryogen outlet 13 connected to the compressor 10 return line 16. The alternating pressure and mass flow produced by compressor 10 and pressure oscillator 20 constitutes pressure/vol-

ume (PV) work, causing regenerator 60 to pump heat from the cooling load to the heat sink, where the heat is ultimately rejected. The result of this heat pumping action is to lower the temperature of the cooling load. Meanwhile, the PV work travels down pulse tube 70, where it is rejected as heat to the heat sink.

[0022] Regenerator 60 is typically filled with a stack of screens which acts as a thermal sponge, alternately absorbing heat from the cryogen and rejecting the absorbed heat back to the cryogen as the pressure oscillates. Pulse tube 70 is a thin-walled tube of a lower thermal conductivity material, such as stainless steel. Pulse tube 70 has screen regions, preferably of copper, at both the hot and cold ends. The two screen regions typically are thermally connected to copper blocks to form the cold and hot end heat exchangers of the pulse tube.

[0023] Figures 4a and 4b show a side cut-away and top view, respectively, of the integrated buffer volume and pressure control housing 80 of the single-stage embodiment of the invention. The motor 30 mounts within a motor chamber, and the valve 20 is connected to the motor shaft. A valve disk 21 is attached to the valve 20, with gas passage holes 22 allowing gas to pass through the valve body 20 and disk 21. The section above the housing 80 is not shown, but would be mounted above the housing 80 in this figure, so that gas from the valve disk 21 holes 22 would pass to and from that section.

[0024] Referring to FIG. 2, a two-stage cryorefrigeration apparatus of the invention includes a first cooling stage 90 and a second cooling stage 100, the first cooling stage 90 having a first stage temperature which is higher than a second stage temperature of the second cooling stage 100. The two-stage cryorefrigerator includes a rotary valve 20 and motor 30 for controlling pressure oscillation, and a primary reservoir 50 and a secondary reservoir 51, all integrated within housing 80. Thus, housing 80 integrates the housing for pressure oscillation means 20 and its power source 30 with the reservoirs 50 and 51, thereby forming a single integrated unit. Optionally, the secondary reservoir 51 is externally located, as will be discussed below.

[0025] The integrated motor housing and reservoir is made from any suitable material capable of withstanding high pressure (*i.e.*, greater than 300 psig). As in the single-stage embodiment, these materials include copper, brass, bronze, stainless steel or aluminum, and in a preferred embodiment preferably 6061-T6 aluminum.

[0026] In addition to the components of the single-stage pulse tube cryorefrigerator, the two-stage cryorefrigeration apparatus of the invention includes first and second stage regenerators 61 and 62, and first and second stage pulse tubes 71 and 72.

[0027] The lower-temperature second stage pulse tube 72 is connected in series or parallel with the cold end of first stage pulse tube 71. In operation, compressor 10 supplies a continuous pressure wave to first stage regenerator 61. After providing cooling in the first stage regenerator 61, the pressure wave provides fur-

ther cooling in second stage regenerator 62, with the cold end of second stage second stage pulse tube 72 being in thermal contact with the cooling load (not shown). The pressure wave continues through the two pulse tubes 71 and 72, and the PV work is rejected as heat to the heat sink.

[0028] Figure 3 shows a perspective view of the cryorefrigerator of the invention, in a two-stage embodiment corresponding to the cut-away and top drawings of figures 5a and 5b. At the top is the secondary buffer volume 51 housing, which is mounted to the integrated pressure control / buffer volume housing 80. The inlet 11 for refrigerant gas and electrical connector 82 for the pressure control extend from the side of housing 80. A lower section 81 provides connection to the gas outlet 13. The pulse tube 71 and 72 and regenerators 61 and 62 extend below the lower section 81. A flange 83 allows the lower part of the cryorefrigerator (pulse tubes and regenerators) to be suspended within a vacuum tank for insulation (not shown).

[0029] Referring to figures 5a and 5b, the cutaway view of figure 5a is shown inverted relative to the complete view of figure 3, so that the secondary buffer volume 51 is on the bottom. It can be seen that the secondary reservoir or buffer volume 51 is mounted to the housing 80, with a gas-tight joint. The motor 30 mounts within a motor chamber, and the valve 20 is connected to the motor shaft. A valve disk 21 is attached to the valve 20, with gas passage holes 22 allowing gas to pass through the valve body 20 and disk 21. The lower section 81 is not shown, but would be mounted above the housing 80 in this figure, so that gas from the valve disk 21 holes 22 would pass to and from the lower section 81.

[0030] Figure 5b also shows that additional buffer volumes 52 and 53 could be optionally be incorporated into the primary housing 80, for use in two-stage, three-stage or higher embodiments. Also, although the buffer volumes 50, 52 and 53 are shown as round bores in the housing 80, it will be understood by one skilled in the art that the buffer volumes could be oval, rectangular, or any regular or irregular shape desired, depending on the volume needed and the configuration of the motor/valve chambers and other elements incorporated into the housing.

[0031] Figures 6a and 6b show an alternate housing for a two-stage cryorefrigerator. The parts are all as described for the embodiment of figures 3, 5a and 5b, with the exception that the secondary reservoir 51 is contained in a separate housing 54 mounted to the side of the main housing 80, instead of to the end of the housing 80 as shown in the embodiment of figures 5a and 5b. In figure 6b, it is seen that primary buffer volume 50 can be rectangular in shape, although as discussed above, the shape might vary widely within the teachings of the invention, depending on the specific needs of the embodiment.

[0032] Accordingly, it is to be understood that the em-

embodiments of the invention herein described are merely illustrative of the application of the principles of the invention. Reference herein to details of the illustrated embodiments is not intended to limit the scope of the claims, which themselves recite those features regarded as essential to the invention.

Claims

1. A cryorefrigeration apparatus having an integrated pressure oscillation controller and buffer volume housing comprising:
 - a) a body;
 - b) a pressure oscillation controller contained in a chamber within the body;
 - c) at least one reservoir providing a buffer volume to receive gas, contained within the body.
2. The cryorefrigeration apparatus of claim 1, further comprising:
 - d) at least one pulse tube; and
 - e) at least one regenerator, the pulse tube and regenerator being operationally connected to the integrated pressure oscillation controller and buffer volume housing.
3. The cryorefrigeration apparatus of claim 1, in which there are at least a first reservoir and a second reservoir contained within the body of the housing.
4. The cryorefrigeration apparatus of claim 1, in which there are at least a first reservoir and a second reservoir, and wherein at least one of the first reservoir and second reservoirs is contained in the body, and the other is external to the body in gas-tight communication therewith.
5. The cryorefrigeration apparatus of claim 1, in which the pressure oscillation controller comprises a rotary valve rotated by a motor.
6. The cryorefrigeration apparatus of claim 5, in which the rotary valve is in a valve chamber in the body.
7. The cryorefrigeration apparatus of claim 5, in which the motor is in a motor chamber in the body.
8. The cryorefrigeration apparatus of claim 1, in which the buffer volume housing further comprises at least one orifice in close proximity to at least one reservoir.
9. The cryorefrigeration apparatus of claim 8, in which the buffer volume housing further comprises at least one flow channel connecting the orifice to at least one reservoir.
10. The cryorefrigeration apparatus of claim 1, in which the buffer volume housing further comprises at least one flow channel connecting at least one reservoir to the pressure oscillation controller.
11. An integrated pressure oscillation controller and buffer volume housing for a cryorefrigerator comprising:
 - a) a body;
 - b) a pressure oscillation controller contained in a chamber within the body;
 - c) at least one reservoir providing a buffer volume to receive gas, contained within the body.
12. The housing of claim 11, in which there are at least a first reservoir and a second reservoir contained within the body of the housing.
13. The housing of claim 11, in which there are at least a first reservoir and a second reservoir, and wherein at least one of the first reservoir and second reservoirs is contained in the body, and the other is external to the body in gas-tight communication therewith.
14. The housing of claim 11, in which the pressure oscillation controller comprises a rotary valve rotated by a motor.
15. The housing of claim 14, in which the rotary valve is in a valve chamber in the body.
16. The housing of claim 14, in which the motor is in a motor chamber in the body.
17. The housing of claim 11, further comprising at least one orifice in close proximity to at least one reservoir.
18. The housing of claim 17, further comprising at least one flow channel connecting the orifice to at least one reservoir.
19. The housing of claim 11, further comprising at least one flow channel connecting at least one reservoir to the pressure oscillation controller.
20. A two-stage cryorefrigeration apparatus, comprising:

- a) a first cooling stage and a second cooling stage, said first cooling stage having a first stage temperature which is higher than a second stage temperature of said second cooling stage; 5
- b) an integrated pressure oscillation controller and buffer volume housing in operative communication with the first cooling stage and the second cooling stage, comprising: 10
- i) a body; ,
- ii) a pressure oscillation controller contained in a chamber within the body; 15
- ii) at least one reservoir providing a buffer volume to receive gas, contained within the body. 20
21. The cryorefrigeration apparatus of claim 20, in which there are at least a first reservoir and a second reservoir contained within the body of the housing. 25
22. The cryorefrigeration apparatus of claim 20, in which there are at least a first reservoir and a second reservoir, and wherein at least one of the first reservoir and second reservoirs is contained in the body, and the other is external to the body in gas-tight communication therewith. 30
23. The cryorefrigeration apparatus of claim 20, in which the pressure oscillation controller comprises a rotary valve rotated by a motor. 35
24. The cryorefrigeration apparatus of claim 23, in which the rotary valve is in a valve chamber in the body. 40
25. The cryorefrigeration apparatus of claim 23, in which the motor is in a motor chamber in the body. 45
26. The cryorefrigeration apparatus of claim 20, in which the buffer volume housing further comprises at least one orifice in close proximity to at least one reservoir. 50
27. The cryorefrigeration apparatus of claim 26, in which the buffer volume housing further comprises at least one flow channel connecting the orifice to at least one reservoir. 55
28. The cryorefrigeration apparatus of claim 20, in which the buffer volume housing further comprises at least one flow channel connecting at least one reservoir to the pressure oscillation controller.

29. A three-stage cryorefrigeration apparatus, comprising:

a) a first cooling stage, a second cooling stage, and a third cooling stage, said first cooling stage having a first stage temperature which is higher than a second stage temperature of said second cooling stage and said third stage having a third stage temperature which is lower than the second stage temperature;

b) an integrated pressure oscillation controller and buffer volume housing in operative communication with the first cooling stage, the second cooling stage and the third cooling stage, comprising:

i) a body;

ii) a pressure oscillation controller contained in a chamber within the body;

ii) at least one reservoir providing a buffer volume to receive gas, contained within the body.

30. The cryorefrigeration apparatus of claim 29, in which there are at least a first reservoir, a second reservoir and a third reservoir contained within the body of the housing.

31. The cryorefrigeration apparatus of claim 29, in which there are at least a first reservoir, a second reservoir and a third reservoir, and wherein at least one of the first reservoir, second reservoir, and third reservoir is contained in the body, and at least one of the other reservoirs is external to the body in gas-tight communication therewith.

32. The cryorefrigeration apparatus of claim 29, in which the pressure oscillation controller comprises a rotary valve rotated by a motor.

33. The cryorefrigeration apparatus of claim 32, in which the rotary valve is in a valve chamber in the body.

34. The cryorefrigeration apparatus of claim 32, in which the motor is in a motor chamber in the body.

35. The cryorefrigeration apparatus of claim 29, in which the buffer volume housing further comprises at least one orifice in close proximity to at least one reservoir.

36. The cryorefrigeration apparatus of claim 35, in which the buffer volume housing further comprises at least one flow channel connecting the orifice to

at least one reservoir.

37. The cryorefrigeration apparatus of claim 29, in which the buffer volume housing further comprises at least one flow channel connecting at least one reservoir to the pressure oscillation controller. 5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




Fig. 3




Fig. 4a




Fig. 4b




Fig. 5a




Fig. 5b




Fig. 6a





Fig. 6b





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 4519

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
E	US 2001/015068 A1 (CHUNG WOO SUK ET AL) 23 August 2001 (2001-08-23) * the whole document *	1,2,11	F25B9/14 F02G1/04
X	US 5 794 450 A (ALEXANDER ARTHUR RAY) 18 August 1998 (1998-08-18) * the whole document * * figure 1 *	1,11	
X	US 5 787 712 A (FUKUI NAOKI ET AL) 4 August 1998 (1998-08-04) * the whole document *	1,11	
X	US 5 488 830 A (BURT WILLIAM W) 6 February 1996 (1996-02-06) * the whole document *	1-3,8,9, 11,12, 17,18	
Y	* column 4, line 15 - line 22 *	20,21, 29,30	
X	EP 0 614 059 A (CRYOTECHNOLOGIES) 7 September 1994 (1994-09-07) * the whole document *	1,2, 8-11, 17-19	TECHNICAL FIELDS SEARCHED (Int.Cl.7) F25B F02G
Y	* column 8, line 42 - line 52; figure 6 *	20, 26-29, 35-37	
X	FR 2 736 710 A (COMMISSARIAT ENERGIE ATOMIQUE) 17 January 1997 (1997-01-17) * the whole document *	1,2,5-9, 11,14-18 20, 23-25, 29,32-34	
Y	US 5 711 156 A (INOUE TATSUO ET AL) 27 January 1998 (1998-01-27) * the whole document *	20,21, 23-28	
-/-			
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 5 November 2001	Examiner Busuiocescu, B
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application I: document cited for other reasons &: member of the same patent family, corresponding document			

EPO FORM 503 01 92 (P4/C21)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 01 30 4519

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)
Y	US 5 107 683 A (CHAN CHUNG K ET AL) 28 April 1992 (1992-04-28) * the whole document *	29, 30, 32-37	
A	GB 2 318 176 A (TOKYO SHIBAURA ELECTRIC CO) 15 April 1998 (1998-04-15) * the whole document *	1-37	
A	US 3 128 605 A (MALAKER STEPHEN F ET AL) 14 April 1964 (1964-04-14) * the whole document *		
A	US 5 412 952 A (OHTANI YASUMI ET AL) 9 May 1995 (1995-05-09) * the whole document *		
A	US 5 901 737 A (YARON RAN) 11 May 1999 (1999-05-11) * the whole document *		
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.CI.7)
Place of search THE HAGUE		Date of completion of the search 5 November 2001	Examiner Busuiocescu, B
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons A : technological background O : non-written disclosure P : intermediate document S : member of the same patent family, corresponding document	

EPO FORM 1603 33/32 (P04051)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 01 30 4519

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

05-11-2001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2001015068 A1	23-08-2001	DE 10105489 A1	06-09-2001
		JP 2001227831 A	24-08-2001
		NL 1017347 A1	20-08-2001
US 5794450 A	18-08-1998	NONE	
US 5787712 A	04-08-1998	JP 2785769 B2	13-08-1998
		JP 9133420 A	20-05-1997
US 5488830 A	06-02-1996	NONE	
EP 0614059 A	07-09-1994	FR 2702269 A1	09-09-1994
		DE 69415187 D1	28-01-1999
		DE 69415187 T2	20-05-1999
		EP 0614059 A1	07-09-1994
FR 2736710 A	17-01-1997	FR 2736710 A1	17-01-1997
		EP 0838012 A1	29-04-1998
		WO 9703327 A1	30-01-1997
		JP 11508991 T	03-08-1999
US 5711156 A	27-01-1998	JP 9033124 A	07-02-1997
US 5107683 A	28-04-1992	NONE	
GB 2318176 A	15-04-1998	JP 8313094 A	29-11-1996
		JP 8313095 A	29-11-1996
		JP 9036442 A	07-02-1997
		GB 2301426 A ,B	04-12-1996
		US 5711157 A	27-01-1998
US 3128605 A	14-04-1964	DE 1426983 A1	04-06-1969
		FR 1389471 A	09-06-1965
		GB 990667 A	28-04-1965
		NL 298732 A	
US 5412952 A	09-05-1995	JP 3152742 B2	03-04-2001
		JP 5322340 A	07-12-1993
		JP 3152757 B2	03-04-2001
		JP 6101916 A	12-04-1994
		US 5335505 A	09-08-1994
US 5901737 A	11-05-1999	NONE	

EPC FORM 2546

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82